AYDIV. 1	COLLEGE	OF	ENGINEERING A	AND	TECHNOI	LOGY	 	NIV	ER	SIT	Y	QUESTION
× ×			\mathbf{R}	leg.	No.:							

Question Paper Code: 11201

B.E./B.Tech. DEGREE EXAMINATION, NOVEMBER/DECEMBER 2012.

Seventh Semester

Civil Engineering

CE 2403/CE 73 — BASICS OF DYNAMICS AND ASEISMIC DESIGN

(Regulation 2008)

Time: Three hours

Maximum: 100 marks

(IS 1893 and IS 13920 codes are permitted)

Answer ALL questions.

PART A — $(10 \times 2 = 20 \text{ marks})$

- (1) Explain Frequency Ratio.
- (2) Explain Critical Damping.
 - 3. Describe briefly the modal super position method.
- 4. What is the fundamental frequency and fundamental mode?
- 5. What is Elastic rebound theory?
- 6. Explain Modified Mercalli Intensity.
- 7. Describe dynamic behavior of soil.
- 8. Explain settlement of dry sand.
- 9. What is meant by Occupancy factor?
- 10. Explain Story drift.

PART B — $(5 \times 16 = 80 \text{ marks})$

11. (a) Show that the log-decrement is also given by the equation $S = 1/n \log (U_o/U_n)$ where U_n'' represents the amplitude after n'' cycles have elapsed.

Or

- (b) A machine foundation weighs 60 KN. The spring constant is 11000 KN/M and dash pot (damper) constant C = 200 KN S/M. Determine,
 - (i) whether the system is over damped, undamped or critically damped
 - (ii) logarithmic decrement
 - (iii) ratio of two successive amplitudes
 - (iv) damped natural frequency
 - (v) if the initial displacement is 10 mm and initial velocity is zero displacement at t = 0.1 S.
- 12. (a) State and prove the orthogonality property of mode shapes.

Or

- (b) In a two storeyed building frame, the mass, M1 = M2 = 1000 Kg, and stiffnesses are K1 = K2 = 1 MN/M. If a horizontal force of 20 KN is applied at the top of ground storey level, determine the displacement of masses Ml and M2.
- (a) Describe the two approaches followed for the prediction of earthquakes.
 Name the major plates of the earth.

Or

- (b) On what is the assignment of an earthquakes magnitude based? Is magnitude the same as intensity? Explain.
- 14. (a) Describe briefly the factor affecting liquefaction characteristics.

Or

- (b) Derive an expression for the condition which a structure will sink during earthquake.
- 15. (a) What is the effect of ignoring the contribution of masonry infill in the lateral load analysis of a multi-storey frame?

Or

(b) In what manner is the behavior of a soft storey construction likely to be different from a regular construction in the event of an earthquake?